

MONO[®]

MONO[®] ACOUSTICAL SEALANT

Revised: 4/21/10

MONO[®] Acoustical Sealant

- For use in sound transmission and sealing wall penetrations
- Easy to gun
- Single-component
- Long lasting
- Excellent adhesion
- Does not stain or bleed
- Remains flexible
- Non-skinning

Packaging: 300 mL, 850 mL
Color: Dark Grey
UPC Number: 0 63213 00695 5, 0 63213 00690 0
DAP Reference Number: 7079875695, 7079875690, 7079875818
SKU Number: 93170X2323, 93170X2334, 93170X2312

Company Identification:

Manufactured For: DAP Canada, 475 Finchdene Sq., Unit 5, Scarborough, ON M1X 1B7
Usage Information: Call 1-888-327-8477 or visit monosealants.ca
Order Information: 416-321-1522
Fax Number: 416-321-3325

Product Description:

MONO[®] Acoustical Sealant is a single-component, non-skinning, non-hardening synthetic butyl rubber sealant for use in reducing sound transmission in drywall partitions and for sealing wall penetrations. Provides an effective adhesive seal for air and vapour barriers. MONO[®] Acoustical Sealant meets CAN/CGSB 19.21 M87 specifications.

Surface Preparation & Application:

1. All surfaces must be clean, dry and completely free of old caulk.
2. Trim nozzle at 30° angle to desired bead size.
3. Puncture inner seal at the base of the nozzle.
4. Load into caulking gun.
5. Fill joint with sealant, pushing sealant ahead of nozzle.

For best results:

- Apply in temperatures above 5°C (40°F).
- This product is intended for captive applications only. It is not to be used for exposed interior applications as the product does not cure and will track on interior finishes.

- *Not recommended for exterior applications.*
- *Joint size should not exceed 20 mm x 13 mm (3/4" x 1/2"). Parallel beads of sealant may be applied to double layer drywall partition assembly to increase sound deadening.*
- *Store sealant away from extreme heat or cold.*

Physical & Chemical Characteristics:

Tooling Time:	Indefinite, material does not skin or cure
Tack-Free Time:	Remains pliable, does not become tack free
Paintable:	Not paintable
Odor:	Naptha
Consistency:	Non-sag, gunnable paste
Vehicle:	Rubber
Volatile Weight:	9%
Flash Point:	Not established
Filler:	Mineral extender
Specific Gravity:	1.62
Solids:	91%
Density:	1720 kg/m ² (13.51 lbs/gallon)
Temperature Service Range:	-40°C to 38°C (-40°F to 100°F)
Temperature Application Range:	5°C to 35°C (40°F to 120°F)
Freeze Thaw Stability:	Stable
Shelf Life:	12 months
Coverage (850 mL cartridge):	Approx. 8.23m (27 linear ft.) of a 6.35mm (1/4") bead
MSDS No:	00042435604

Clean Up:

Immediately remove all excess sealant or smears adjacent to joint edges as work progresses using xylene or mineral spirits. Any utensils used for tooling can also be cleaned with xylene or mineral spirits. Do not use xylene or mineral spirits to clean skin.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at www.monosealants.ca or by calling 416-321-1522.

Satisfaction Guaranteed:

If not satisfied with product performance when used as directed within one year of purchase, DAP Canada will replace this product or refund your purchase price. Call 416-321-1522 with your sales receipt and product container available to arrange for warranty fulfillment. DAP Canada and its affiliates will not be liable for any incidental or consequential damages under any circumstances.